

Large Venue Projector

Vivitek D5110W

WXGA High Brightness Installation Projector



Features

- 5,000 ANSI lumens with a 2,000 contrast ratio
- Native WXGA resolution with a maximum WUXGA resolution
- Centered lens for easy installation
- Horizontal and vertical lens shift
- Connectivity options including: HDMI v1.4, DisplayPort, VGA-Out, RJ45 and RS-232C
- Built-in 12V trigger for external wireless module connection
- Three Interchangeable lens options for greater installation flexibility
- Network ready for integration and system administration via RJ45
- Crestron® RoomView certified for easy communications and remote control over an IT network
- Keypad lock prevents accidental system adjustments
- Convenient side loading lamp door design for quick and easy replacement

Photos



Specifications *Standard Lens

Display Type	Single 0.65" DLP Technology by TI
Brightness	5000 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	WUXGA (1920x1200) @60Hz
Contrast Ratio	2,000:1
Lamp Life/Type	1500/3500 hours (Normal/Eco Mode) 370W/280W
Throw Ratio*	1.62 - 2.03:1
Image Size (Diagonal)*	34.3" - 200"
Projection Distance*	1.5 - 7 m (4.92ft to 23ft)
Projection Lens*	F =2.46 - 2.56, f=22.8 - 28.5mm
Zoom Ratio*	1.25x
Aspect Ratio	16:10
Offset	Vertical -15% /+ 55%
Keystone Correction	Vertical ±40°
Horizontal Frequency	15, 31 – 91.4kHz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D Compatibility	Yes (Supports DLP Link, Blu-Ray 3D)
Speakers	3W x 2 (Stereo)
Lens Shift Range	Vertical -15%/+55%, Horizontal +/-5%
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.4b, DisplayPort, DVI-D, Component (5 BNC) (RGBHV), Component (YPbPr –RCA x3), VGA-In (x2), S-Video, Composite Video, Audio-In RCA (L/R)(x2), Audio-In (Mini-Jack)(x2), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V Trigger, 3D Sync-Out, RS-232C, USB Power (5V, 1.5A), USB (Service), Remote Jack (Wire Remote)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x H)	431 x 344 x 180mm (17"x 13.5" x 7.1")
Weight	8.6 kg (19 lbs)
Noise Level	42dB/37dB (Normal/Eco Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	450W (Normal Mode), 340W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	Replacement Lamp, Interchangeable Lens (x5), Anti-Dust Filter (China Only)

Lens Details

Lens	Short Throw	Std Short Throw	Standard
Throw Ratio	0.81:1	1.15 - 1.36:1	1.62-2.03:1
Zoom Ratio	N/A	1.18x	1.25x
F Value	11.5mm	16.64 – 19.54mm	22.8 - 28.5mm
F#	2.5	2.05 – 2.27	2.46 - 2.56
Screen Size	25" – 200"	30" – 300"	30" – 300"
Projection Distance	0.5 - 3.0m	1 - 9m	1.5 - 3m

Lens	Long Throw	Super Long Throw
Throw Ratio	2.02-3.05:1	3.15 – 5:25:1
Zoom Ratio	1.5x	1.67x
F Value	28.5 - 42.75mm	44.5 – 74.19mm
F#	2.5 - 3.1	2.2 – 2.5
Screen Size	30" – 500"	35" – 400"
Projection Distance	2.0 - 20m	3~20m

©2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

