

Multimedia Projector

Vivitek DU978WT

High brightness WUXGA multimedia projector for the best presentations



Features

- High brightness of 5,000 ANSI lumens and high 15,000:1 contrast ratio for the best quality, sharpness and clarity of a video
- Widescreen WUXGA resolution perfect for HD multimedia presentations and movies
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images
- Vertical lens shift and 1.5x zoom ratio for greater installation convenience and flexibility
- 5 segment RYGBW color wheel for improved and vivid color reproduction
- Assortment of video (HDMI 1.4b, DisplayPort, VGA, S-Video, Composite Video), communication (RJ45, USB, RS232, 12v trigger) and audio (audio-in/out) I/O options for simplified device connectivity
- Extend lamp life with an energy efficient lamp that deliver up to 4,000 hours of usage (Dynamic Eco. Mode)
- Project 3D content from DLP® Link™, and BluRay HDMI 1.4b for realistic life-like images
- Built-in 3W audio speaker with multiple audio-in and audio-out ports
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Choice of 8 pre-set display scenario modes including presentation, bright, game, movie, TV, sRGB, blackboard and user
- Anti-theft security features include: Kensington® security slot, security bar, and password protected keypad lock

Specifications

Display Type	Single 0.67" DLP Technology by TI
Brightness	5,000 ANSI Lumens
Native Resolution	WUXGA (1920 x 1200)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	15,000:1
Lamp Life/Type	2500/3500/4000 Hours (Normal /Eco/Dynamic Eco Mode) 310W/245W
Throw Ratio	1.39 – 2.09
Image Size (Diagonal)	26.6" - 334"
Projection Distance	1.2m - 10m (3.97' to 32.8')
Projection Lens	F/#2.42 - 2.97, f=20.9 - 31.05
Zoom Ratio	1.5x
Aspect Ratio	16:10 Native
Offset (Vertical)	122% ±10%
Keystone Correction	Vertical ±30°
Vertical Lens Shift	Yes
Horizontal Frequency	15, 31 – 91Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
Lens Shift Range	Vertical:118.9%±5% - 131%±5%
3D Compatibility	Yes (DLP® Link™, HDMI 1.4b (BluRay))
Audio	3W (Mono)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In (x2), HDMI v1.4 (x2), DisplayPort, S-Video, Composite Video, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V-Trigger, RS-232, 3D-Sync-Out, Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	332.8 x 255 x 114.6mm (13.1 "x 10" x 4.5")
Weight	3.95kg (8.7lbs)
Available Color	White
Noise Level	36dB/30dB (Normal/Eco. Mode)
Power Supply	AC 110-240V, 50/60Hz
Power Consumption	370W (Normal Mode), 300W (Eco. Mode), <0.5W (Standby Mode) , <6W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Carry Case, Documentation Kit
Optional Accessories	Replacement Lamp, Filter

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

Photos

