



VS-66UHD

6x6 4K60 4:2:0 Matrix Switcher

| HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:2:0)



VS-66UHD is a high-quality 6x6 matrix switcher for 4K@60Hz (4:2:0) HDMI signals and embedded audio. It reclocks and equalizes the signals and can route any one of six HDMI, HDCP-compliant sources (selectable) to any or all outputs simultaneously. VS-66UHD offers a flexible audio scheme where any HDMI digital audio input can be routed to any HDMI digital audio output in addition to ARC support to produce an equivalent 12x9 audio matrix

FEATURES

Max. Data Rate - 8.91Gbps data rate (2.97Gbps per graphics channel)

Max. Resolution - 4K@60Hz (4:2:0)

Independent 12x9 Audio Matrix - With 6 embedded digital inputs + 6 ARC inputs and 6 digital outputs + 3 ARC outputs

Kramer Step-In Over HDMI Technology

HDMI, HDCP and DVI Compliance

Selectable HDCP Off per Input

Memory Locations - 12 presets for quick access to common configurations

Advanced EDID Management per Input

Active Source & Acceptor Detection

Automatic Input Selection - Based on priority selection or last connected input

HDMI Support - Deep Color, 3D, ARC, up to 7.1 uncompressed audio channels

Kramer reClocking™ and Equalization Technology - Rebuilds the digital signal to travel longer distances

Embedded Pattern Generator - With selectable patterns

Lock Button - To prevent tampering

Kramer Protocol 3000 Support

Firmware Upgrade - Via mini USB, Ethernet or the RS-232 port

Control Options - RS-232 serial commands transmitted by a PC, touch screen system or other serial controller, Ethernet port via LAN, embedded Web pages via LAN for configuration and control

Size - Standard 19" (1U). Rack "ears" included



KRAMER

TECHNICAL SPECIFICATIONS

Inputs	6 HDMI On female HDMI connectors
Outputs	6 HDMI On female HDMI connectors
Ports	1 Programming On a Mini-USB connector 1 RS-232 On a 3-pin terminal block connector 1 Ethernet On an RJ-45 connector 1 USB On a USB-type A connector for powering an external device
Video	Max. Resolutions 4K@60Hz (4:2:0) and 4K@30Hz (4:4:4) Standards Compliance HDCP 1.4
User Interface	Indicators OUTPUT/INPUT LED Display Control Front panel buttons, RS-232, Ethernet remote connection
Power	Source 100-240V/50-60Hz Consumption 500mA
Environmental Conditions	Operating Temperature 0° to +40°C (32° to 104°F) Storage Temperature -40° to +70°C (-40° to 158°F) Humidity 10% to 90%, RH (non-condensing)
Accessories	Included Rack ears, power cord
Product Dimension	19" x 9.34 x 1U (43.6cm x 23.72cm x 4.36cm) W, D, H
Product Weight	2.4kg (5.3lbs) approx
Shipping Dimension	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
Shipping Weight	3.3kg (7.3lbs) approx

