

VS-21DT

2x1 4K60 4:2:0 HDCP 2.2 HDMI Auto Switcher over HDBaseT | HDMI | HDCP Compliant | HDBaseT | 4K/60 UHD (4:2:0) | HDCP 2.2 Compatible





VS-21DT is a high-performance automatic switcher for 4K, HDBaseT, HDMI, HDCP 2.2 video signals. Offering priority and last-connected switching options, it automatically switches according to the selected switching scheme based on active video signal detection

FEATURES

Max. Data Rate - 8.91Gbps (2.97Gbps per data channel)

Max. Resolution - 4K@60Hz (4:2:0)

HDCP 2.2 Compliant

Supports up to 40m reach at 4K@60Hz (4:2:0) Kramer Equalization and re-Klocking Technology

HDTV Compatible

3D Pass-Though



TECHNICAL SPECIFICATIONS

Inputs 2 HDMI On female HDMI connectors

Outputs 1 HDBT On an RJ-45 connector

Video Max. Data Rate 8.91Gbps (2.97Gbps per graphic channel)

Max. Resolution 4K@60Hz (4:2:0)

Standards Compliance HDCP 2.2 (does not support conversion to HDCP 1.4)

User Interface Controls DIP-switches for selecting switching mode (Priority/Last Connected),

contact closure connectors for remote control switches

Indicators Active input, switching mode (Priority/Last Connected) and ON

Power Source 5V DC

Consumption 1A

REGULATORY CERTIFICATION:

 $EMC\ EN\ 55032; IEC\ 60950-1 (ed.2); IEC\ 60950-1 (ed.2) am1; IEC\ 60950-1 (ed.2) am2$

Environmental Conditions

Operating Temperature 0 $^{\circ}$ to +40 $^{\circ}$ C (32 $^{\circ}$ to 104 $^{\circ}$ F)

Storage Temperature -40° to +70°C (-40° to 158°F)

Humidity 10% to 90%, RHL non-condensing

Accessories Included 5V DC power adapter

Product Dimension 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimension 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

Shipping Weight 0.5kg (1.1lbs) approx

