CPLUS-V4H2HA




This 4K60 4 by 2 Matrix provides the ability to connect up to four 4K60 HDMl sources to up to two 4K60 HDMl displays and freely switch between them. This unit comes with full support for $4 \mbox{K}@60\mbox{Hz}$ (4:4:4, 8- bit) as well as support for 16-bit Deep Color, HDR (High Dynamic Range), 3D content, HD audio and other features defined by HDMl 2.0 specification. Pre-defined internal EDIDs and external EDIDs option are available for EDID managing. The matrix also supports auto source switch and display control for power on/off the connected devices by sending CEC or RS-232 commands. Control is provided via front-panel buttons, RS-232, and IR remote.

PANELS



DIAGRAM



FEATURES

- Supports UHD⁺ resolutions up to 4096x2160@60Hz (YUV 4:4:4, 8 bit)
- Supports 16-bit Deep Color up to 1080@60Hz
- Supports pass-through of audio formats including LPCM 2.0/5.1/7.1, Bitstream, and HD Bitstream
- · Support internal EDIDs and external EDIDs options .
- Support Auto Source Switch
- Basic signal event automation via RS-232 or CEC.

SPECIFICATIONS

Interfaces

IIILEITACES			
Input Port	4 x HDMI		
Output Port	2 x HDMI 1 x Stereo (3.5mm)		
Service Port	1 x USB 2.0 (mini B)		
Video			
HDMI Compliance	HDMI 2.0 (DVI 1.0)		
HDCP Compliance	2.x		
Input Signal Types	4096 x 2160p@60 8-bit YUV 4:4:4,HDR 10		
Output Signal Types	4096 x 2160p@60 8-bit YUV 4:4:4,HDR 10		
	Resolutions		
Maximum Input	HDMI	4096×2160p@60	
Maximum Output	HDMI	4096×2160p@60	
Audio			
Input Signal Types	HDMI		
Output Signal Types	HDMI, Unbalanced Stereo		
Digital Formats	HDMI 7.1 CH LPCM, Bitstream, HD Bitstream		
Power			
Power Supply	5V/2.6A		
Power Consumption	8.62W		
Enclosure			
Chassis Material	Metal (Stee	1)	
Chassis Color	Black		
Dimensions (W×H×D)	231.5mm×25mm×108mm [Case Only] 231.5mm×25mm×117mm [All Inclusive]		
Weight	620g		
Field Firmware Update			

Micro-USB to PC

ORDERING INFORMATION

Model No.	Product Description		
CPLUS-V4H2HA	UHD ⁺ 4x2 HDMI Matrix with Audio Output		

