

VANZEL

MINI HDMI to AV



USER Manual

model : IC-H2C

Table of Contents

1.0 Introduction

2.0 Specifications

3.0 Package Contents

4.0 Panel Descriptions

5.0 Connection Diagram

2

1.0 Introduction

The MINI HDMI to AV audio signal converter can convert HDMI video signal or audio signal to AV composite video signal and the FL / FR stereo audio signal, can convert the high quality HDMI video signal into normal CVBS signal (standard-definition 480i, 576i,) Which can play on TV, VHS VCR, DVD recorders, etc, and support NTSC, PAL TV format

1.1 Features

- 1.No need to install drivers, portable, flexible, plug and play.
- 2.Low power, No power adapter.

3

3. Support NTSC and PAL two standard TV formats output

4. Compatible HDMI1.3

2.0 SPECIFICATIONS

1. Input ports: 1xHDMI.

2. Output ports: AV (Yellow, White, Red)

3. Dimensions (mm): 66(D) x 55(W) x 20(H)

4. Weight (g): 40

5. HDMI Input Resolution:

640x480@60Hz, 800x600@60Hz

1024x768@60Hz, 1280x720@60Hz,

1280x1024@60Hz, 1360x768@60Hz,

4

1600x1200@60Hz, 1920x1080@60Hz,
480p/60Hz, 576p/60Hz,
720p50/60Hz, 1080I50/60Hz, 1080p50/60Hz.

6. CVBS output: PAL, NTSC_M, and (NTSC_J)

3.0 PACKAGE CONTENTS


Before attempting to use this item, please check the package and make sure the following items are contained in the shipping carton:

- 1) Main unit (HDMI to AV Convener) ----- 1 PCS
- 2) USB Cable ----- 1 PCS
- 3) User Manual. ----- 1 PCS

4.0 PANEL DESCRIPTIONS

Please check the panel drawings below and become familiar with the signal input(s), output(s) and power requirements.

Back Panel: Top Panel: Front Panel:



5.0 CONNECTION DIAGRAM

