




The HDMI 2 to 1 Switcher allows 2 HDMI sources to be connected to the same HDMI TV/Monitor input. It has both automatic and manual input selection and a 'last memory' function that remembers the last input selection used. The EDID bypass function ensures the best resolution. The switcher is also DVI compatible with the use of DVI to HDMI adaptor.

PANELS



DIAGRAM



2x1 HDMI Switcher

FEATURES

- Supports 24/30/36-bit color depth display Supports Bitstream •
- •
- Auto Signal Enhancement that improve signal quality after long distance • transmission
- Auto input detection with LED indicators
- EDID bypass .
- Supports HDMI 3D signal •
- Supports up to 1920 x 1200p(RB)@60Hz

SPECIFICATIONS

Interfaces			
Input Port	2 x (Type-A)		
Output Port	1 x (Type-A)		
Video			
HDMI Compliance	HDMI 1.4 (DVI 1.0)		
HDCP Compliance	1.4		
Input Signal Types	1080p60 12-bit		
Output Signal Types	1080p60 12-bit		
		Resolutions	
Maximum Input	HDMI	1920×1200p@60RB	
Maximum Output	HDMI	1920×1200p@60RB	
Power			
Power Supply	5 V/1 A DC		
Power Consumption	3.1W		
Enclosure			
Chassis Material	Aluminum		
Chassis Color	Black		
Dimensions (W×H×D)	101 mm x 25 mm x 92 mm		
Weight	196g		
Field Firmware Update			
PCB on board, uses RS232			

ORDERING INFORMATION

Model No.	Product Description
CLUX-21N	2x1 HDMI Switcher