

# 8 / 16 Port 18.5" VGA LCD KVM Switch ( XL1808 / XL1816 )






#### Overview

The Kinan's XL18xx series LCD KVM console features an integrated rackmount monitor, keyboard and touchpad in a single console that occupies only 1U of rack space. It allows access and control up to 8/16 computers from a single console (keyboard, mouse and monitor). The number of connected computers can be increased up to 256/512 by daisy-chaining up to 31 XM0108 KVM Switches.


The XL18xx series keyboard monitor mouse switch has a built-in LCD monitor that supports resolution up to 1366×768@60Hz. Switching between computers can be easily accomplished by front panel pushbuttons, keyboard hotkey combination or on-screen-display (OSD).


The LCD KVM switch supports USB connection for the computers. An extra HDB15 port allows an additional VGA monitor to be connected.



| 1 | LCD Monitor          | 6 Touchpad                |  |
|---|----------------------|---------------------------|--|
| 2 | Rear Bracket Slot    | 7 Handle                  |  |
| 3 | Display Menu Buttons | 8 Release Switch          |  |
| 4 | Mounting Bracket     | 9 Display Panel           |  |
| 5 | Keyboard             | 10 Port Selection Buttons |  |

#### Structure





| 1 | PC Port         | 4 | Ground Connection Screw |
|---|-----------------|---|-------------------------|
| 2 | Power input(AC) | 5 | Cascade port            |
| 3 | Power switch    | 6 | Console Port            |

## **Hardware Features**

- Integrated rack mount drawer with 18.5" LCD monitor, keyboard/touchpad and 8/16 port KVM switch in a 1U height console
- Standard VGA connection-Connect to a server or computer via standard VGA connectors
- LCD module can be opened up to 108 degrees to provide a comfortable viewing angle
- Supports computers with USB and PS/2 keyboard and mouse

### Management

- Convenient computer switching via front panel LEDs, keyboard hotkey combination or on-screen-display (OSD)
- Auto scan feature for monitoring user-selected computer
- Broadcast mode--operations simultaneously performed on all selected computers
- Hot pluggable --add or remove computers without having to power down the switch



- Quickly select your computer by naming the server or inputting SN number of the server
- On-Screen Display (OSD) adjustments-Adjust the on-screen image, including: auto adjust, exit, power on/off, brightness, and menu

#### **High Resolution**

- 18.5" TFT LCD KVM monitor with highlight, high definition and high resolution
- Optimum resolution is up to 1366×768@60Hz

## **Daisy-Chain Connection**

• By daisy-chaining up to another 31 switches, as many as 256/512 servers can be controlled from a single console

#### Security

- Two level password security--only authorized users view and control computers
- Supports one administrator and four user accounts with a separate profile for each

#### **High Performance Touchpad**

Touchpad with scroll wheel - Eliminates the need for a separate, external mouse


## Keyboard

- Multi-language support--English, Russian, German, French, UK and Spanish, etc.
- Full size 99 keys keyboard with integrated number pad

### **Wide Compatibility**

- Multiplatform Support-Compatible with Windows, Linux, Mac and Sun
- Supports servers form Lenovo, HUA WEI, HP, IBM, Cisco and Dell, etc.

## **Connection Diagram**





# **Package Contents**

- 1x LCD Console
- 1x Power Cord (Regional)
- 1x Quick Start Guide
- 2x Mounting Rails
- 8/16x USB+VGA KVM Cable (1.8m/6ft)

## **Specifications**

| Model                          |                         | XL1808 XL1816  |        |  |  |
|--------------------------------|-------------------------|--|--------|--|--|
| Computer                       | Direct                  | 8  | 16     |  |  |
| connections                    | Max                     | 256  | 512    |  |  |
| Port emulation Keyboard, mouse |                         | USB  |        |  |  |
|                                | LCD model               | WXGA TFT   |        |  |  |
|                                | View area               | 18.51"   |        |  |  |
|                                | Optimum resolution      | 1366×768@60Hz  |        |  |  |
| LCD monitor                    | Display color           | 16.7 M   |        |  |  |
|                                | Brightness              | 250cd/m² ( Typ )   |        |  |  |
|                                | Contrast ratio          | 1000:1 ( Typ )   |        |  |  |
|                                | Pixel pitch(mm)         | 0.300(H) × 0.300(W)  |        |  |  |
|                                | X/Y resolution          | >1000 points / inch, (40 points/mm)                              |        |  |  |
| Mouse                          | Touchpad with trackball | Eliminates the need for an external mouse                        |        |  |  |
| Keyboard                       |                         | 99 keys (82 keys main keyboard +17 independent small number pad) |        |  |  |
| Port selection                 |                         | Front panel pushbuttons, hotkeys, OSD menu                       |        |  |  |
| Input power                    |                         | 100V- 240Vac, 50-60Hz, <1.5A                                     |        |  |  |
| Power consumption              |                         | 16W  | 17W    |  |  |
| Operating temperatur           | e                       | 0 − 50 ℃   |        |  |  |
| Store temperature              |                         | -20 <b>−</b> 60 °C   |        |  |  |
| Humidity                       |                         | 0~80% RH, non-condensing   |        |  |  |
| Net weight                     |                         | 11.5kg   | 11.7kg |  |  |
| Product dimension (W           | ′×D×H)                  | 448mm×560mm×42.5mm   |        |  |  |
| Package dimension (W           | / × D × H)              | 765mm×615mm×185mm  |        |  |  |