

HDMI-UC-4K

HDMI to USB-C Converter

FEATURE:

- HDMI 2.0b, HDCP 2.2, and DVI 1.0 compliant
- Support 18Gbps HDMI video bandwidth
- Video resolution up to 4K@60Hz 4:4:4
- Output supports DP1.2
- Up to 7.1CH audio pass-through, supporting PCM, Dolby TrueHD, DTS-HD Master Audio
- Compact in design, plug and play



HDMI-UC-4K

This HDMI to USB-C Converter has 1 HDMI INPUT, 1 HDMI LOOP OUT and 1 USB-C OUTPUT, which can convert HDMI signal to USB-C signal with video resolution up to 4K2K@60Hz 4:4:4. It can work normally without micro USB power supply if the connected USB-C display is powered on. This converter can be widely used in video conference, multi-media broadcasting and other related occasions.



Accessories

HDMI to USB-C Converter

**SPECIFICATIONS:****Technical**

HDMI Compliance	HDMI 2.0b
HDCP Compliance	HDCP 2.2
Video Bandwidth	594MHz/18 Gbps
Video Resolution	HDMI input: Up to 4K@60Hz 4:4:4 HDMI Loop out: 480i ~1080p50/60Hz, 4Kx2K@24/30Hz, 4K2K@60Hz USB-C output: 480p60Hz, 576p50Hz-1080p50/60Hz, 4Kx2K@24/30Hz, 4K2K@60Hz
Color Space	RGB, YCbCr 4:4:4 / 4:2:2, YUV 4:2:0
Color Depth	8/10/12-bit
Audio Format	Up to 7.1CH audio pass-through, supporting PCM, Dolby TrueHD, dts-HD Master Audio

Connections

Input	1xHDMI IN [Type A, 19-pin female]
Output	1xHDMI OUT [Type A, 19-pin female] 1xUSB-C [24-pin female]

Mechanical

Housing	Plastic Enclosure
Color	Black
Dimensions	90mm[W] × 60mm[D] × 16mm[H]
Weight	49g
Power Supply	USB 5V / 1A
Power Consumption	3.2W (Max)
Operation Temperature	32 - 104°F / 0 - 40°C
Storage temperature	-4 - 140°F / -20 - 60°C
Relative Humidity	20 - 90% RH (no condensation)