



## 65B4E31T

### 65" 4K UHD DIGITAL SIGNAGE DISPLAY

Hisense Digital Signage Displays are ideal for retail and business environments. The products are the perfect backbone of a digital broadcasting platform in supermarkets, restaurants, stadiums, shopping malls and office buildings. A combination of seamless design and enhanced 500 nits brightness will ensure your digital content vividly stands out from the crowd.

#### Highlights



##### Smart CMS

Hisense's CMS platform allows you to edit and arrange playlists, making content management easy and user-friendly. It supports all rich media content in synchronous playback over a multitude of commercial displays.



##### Landscape & portrait

Both landscape and portrait orientations are possible, providing you with endless creative and functional possibilities to fulfil your commercial or informative goals.



##### 178° Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for shoppers, employees or visitors that will view B4E31T displays from diverse angles while passing by.



##### Customization

Hisense's B4E31T displays support a variety of on-screen customisations such as custom startup logo, startup animation, wallpaper and many more. Creating a uniform look & feel for all people working with or viewing the displays.



##### Round-the-clock operation

Designed with dual-core System on Chip (SoC) technology the Hisense B4E31T series can be used for broadcasting both offline and cloud based content 18 hours a day, 7 days a week.



##### 4K Ultra HD

The 4K Ultra HD picture quality\* ensures perfect colour and rich details in all possible broadcasting surroundings, ranging from shops, to restaurants and office buildings.



##### 500 nits

With 500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



##### Automatic time zone

When connected to the Internet each display will automatically synchronise to its local timezone. Making sure scheduled media broadcast is always in sync.



## Specifications

### Digital Display Panel

Backlight	DLED
Panel Type	IPS
Size	65"
Resolution	3840 x 2160
Refresh rate	60HZ
Color	1.07G (8 Bits+FRC)
Brightness	500 nits (typ)
Contrast(typ)	1200:1 (typ)
Response time(typ)	8ms (typ)
Viewing angle(Min.)	178°/178°
Color gamut	72%
Haze	1%
Orientation	Landscape & Portrait
Lifetime	50,000Hrs (min)
Operation Hours	7Day x 18Hour

### Power

Input	AC 100V-240V @ 50/60HZ
Power Consumption	200W
Standby consumption	<0.5W (standby mode)

### Physical

Bezel Color	Black
Set Dimension (W×H×D)	1462.3mm x 837.3mm x 93.4mm 57.57 x 33 x 3.68 inch
Bezel width (T/L/R/B)	T/B/L/R:14.9mm
Net Weight	27.6kg / 60.86lbs
Packing Dimension (W×H×D)	1616 x 998 x 187mm 63.62 x 39.3 x 7.36 inch
Packed Weight	31.4kg / 69.24lbs
VESA	400mm x 400mm

### System

OS	Android 8.0
DDR	2G
ROM	16G
Language	English/Chinese/Polish/Russian

### Speaker

Built in speaker	8W x 2
------------------	--------

### Control Method

Remote	IR
RS232	1 x RS232 (RJ45)

### Connectivity

WIFI	Yes
LAN	1 x RJ45
SD /TF Card	1 x TF
USB	1 x USB 2.0 1 x USB3.0
Input	2 x HDMI 2.0 Audio in
Output	Headphone Jack

### Environment

Temperature	0 - 40 °
Humidity	20% - 80%

### What's in the box

Basic	Power cord
	Remote controller
	RS232 cable
	Battery
	User manual
	HDMI Cable

### Certification

Standard Certification	CB/CE/ERP/RCM
EAN	6973172940792
Energy Table	65B4E31T



### Dimensions

**65"** 1462.3 x 837.3 x 93.4 mm / 57.57 x 33 x 3.68 inch  
27.6 kg / 60.86 lbs

