

4x4 4K HDMI Matrix Switch

VM0404HA

- The ATEN VM0404HA 4x4 4K HDMI Matrix Switch supports 4K resolutions of UHD (3840 x 2160) and DCI (4096 x 2160) with refresh rates of 30 Hz (4:4:4) and 60 Hz (4:2:0). Ready for the future of high-definition video switching, the VM0404HA is ideal for applications where the routing of 4K digital signals is required, such as in classrooms, auditoriums, department stores and more.

The VM0404HA matrix switch offers an easy and affordable way to route any of 4 HDMI video sources to any of 4 HDMI displays and can be operated through front-panel pushbuttons, IR remote and RS-232 control, ensuring optimum viewing and control of high-definition video.

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

4K 4096x2160

4K 3840x2160



A/V In
HDMI



A/V Out
HDMI



RS-232 Control



IR Remote Control



EDID



HDCP

Front view



Rear view





Features

- Connects any of 4 HDMI sources to any of 4 HDMI displays
- Supports 4K resolutions up to UHD (3840 x 2160) and DCI (4096 x 2160) with refresh rates of 30 Hz (4:4:4) and 60 Hz (4:2:0)
- EDID Expert™ – selects optimum EDID settings for smooth power-up, high-quality display and use of the best video resolution across different screens
- Multiple Control Methods – system management via front-panel pushbuttons, IR remote and RS-232 control
- Supports Dolby True HD and DTS HD Master audio
- Signaling rates up to 3.4 Gbits for flawless 4K output
- HDMI (3D, Deep Color, 4K) and HDCP 1.4 compatible
- Consumer Electronics Control (CEC) allows interconnected HDMI devices to communicate and respond to a single remote control
- Supports ATEN's LockPro™ HDMI cable lock for secure HDMI cable connections
- ESD protection for HDMI
- Firmware upgradeable
- Rack Mountable (1U design)

Specifications

| Function | VM0404HA |
|----------------------------|--|
| Video Input | |
| Interface | 4 x HDMI Type A Female (Black) |
| Impedance | 100 Ω |
| Max Distance | 1.8 m |
| Video Output | |
| Interface | 4 x HDMI Type A Female (Black) |
| Impedance | 100 Ω |
| Max Distance | 15 m |
| Video | |
| Max Data Rate | 10.2 Gbps (3.4 Gbps Per Lane) |
| Max Pixel Clock | 340 MHz |
| Compliance | HDMI (3D, 4K, Deep Color) HDCP 1.4 Compatible Consumer Electronics Control (CEC) |
| Max Resolution | Up to 4096 x 2160 / 3840 x 2160 @ 60 Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30 Hz (4:4:4) |
| Max Distance | Up to 15 m |
| Control | |
| RS-232 | Connector: 1 x DB-9 Female (Black) Baud Rate and Protocol: Baud Rate: 19200, Data Bits: 8, Stop Bits:1, Parity: No, Flow Control: No |
| USB | 1 x Micro USB, F/W Upgrade |
| IR | 1 x Mini Stereo Jack Female (Black) |
| EDID Settings | EDID Mode: Default / Port1 / Remix |
| Power | |
| Connectors | 1 x DC Jack (Black) |
| Consumption | 5 VDC, 10.58 W |
| Environmental | |
| Operating Temperature | 0° to 40° C |
| Storage Temperature | -20° to 60° C |
| Humidity | 0 - 80% RH, Non-Condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 2.02 kg |
| Dimensions (L x W x H) | 43.72 x 16.29 x 4.40 cm |

