## 2 X6 3G HD/SD-SDI DISTRIBUTION AMPLIFIER

# **VP-597**

VP-597 is a 6 output SDI distribution amplifier with A/B inputs switching control. It supports 3G/HD/SD SDI video with embedded audio and re-clocking for long distance transmission. Two source inputs can be controlled by an A/B panel switch or thru GPI remote control interface.

It is ideal for A/B switching to multiple displays or as a backup 3G/HD/SD SDI source switcher for live events.

## **FEATURES**


- 2 x 3G/HD/SD-SDI inputs
- 6 x 3G/HD/SD-SDI distribution outputs
- Supports embedded Audio SDI
- Supports video formats:
- 3G-SDI | HD-SDI: 1080P 50/59.94/60/ 23.98/24/25/30
- SD-SDI 1080i 50/59.4/60/525i /625i/720P/50/59.94/60
- Two input video sources can be controlled by A/B switch or GPI remote
- DC-12V

## FRONT VIEW





## VP-597 GPI Remote Control



## REAR VIEW



## HD/SD-SDI DISTRIBUTION AMPLIFIER **VP-445**



- Four way HD/SD SDI Distribution Amplifier with Embedded Audio
- Supports multi standard Operation SD-SDI (SMPTE 259M and SMPTE 344M)
- Supports HD-SDI (SMPTE 292M)

- 1 Input / 4 Output
- HD/SD SDI Connections

**FEATURES** 

- Low Power Consumption
- Metal Case


## DIAMENSIONS

Power: DC12V 300mA

Size (mm): 123 (L) x 89 (W) x 25 (H)

Weight: 300g

## FRONT VIEW



## REAR VIEW

