

VP-61xl

6x1 Computer Graphics Video & Balanced Stereo Audio Switcher

| VGA/UXGA - 15-pin HD



The VP-61xl is a high-performance switcher for computer graphics video signals, with resolutions ranging from VGA through UXGA and higher, and balanced stereo audio signals. The VP-61N has all the same features of the VP-61xl but without audio

FEATURES

High Bandwidth - 400MHz (-3dB) HDTV Compatible Control - Front panel & RS-232 (K-Router™ Windows®-based Kramer software is included) Standard 19" Rack Mount Size - 1U



TECHNICAL SPECIFICATIONS

INPUT:	6 analog red, green, blue signals: 0.7Vpp/75 Ω , H & V syncs, TTL level on 15-pin HD (F) connectors; 6 balanced audio stereo signals, +4dBu typical, 24dBu max. on detachable terminal blocks
OUTPUT:	1 analog red, green, blue signal: $0.7Vpp/75\Omega$, H & V syncs, TTL level on a 15-pin HD (F) connector; 1 balanced audio stereo signal, +4dBu typical, 24dBu max. on a detachable terminal block
BANDWIDTH (-3dB):	400MHz (video); 100kHz (audio)
SWITCH TIME:	Less than 5ms
SWITCH CONTROL:	Six electronic illuminated touch switches with electronic interlock. RS-232 via an additional 9-pin D-sub connector on rear panel
COUPLING:	Direct
POWER CONSUMPTION:	230V AC, 50/60Hz, (115V AC, USA) 3VA
INCLUDED ACCESSORIES:	Power cord, Windows®-based Kramer control software
Product Dimension	19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H
Product Weight	2.8kg (6.3lbs) approx
Shipping Dimension	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H
Shipping Weight	3.7kg (8.2lbs) approx

