



1616S-XL

16x16 Analog Balanced Stereo Audio Matrix Switcher

| Ethernet - RJ-45



The Lassen XL Series offers flexibility and adaptability to any application where saving space and costs are important. 1616S-XL is a 16x16 analog balanced stereo audio matrix switcher, available in a compact 2RU frame. It offers control via the front panel or remotely via RS-232 or Ethernet

TECHNICAL SPECIFICATIONS

Inputs	16 Balanced/Unbalanced Stereo Analog Audio: On 5-pin terminal block connectors
Outputs	16 Balanced/Unbalanced Stereo Analog Audio: On 5-pin terminal block connectors
Ports	2 Sync: On BNC connectors
	1 Ethernet: On an RJ-45 connector
	1 RS-232/422: On a 9-pin D-sub connector
	2 RS-485: On male mini-XLR connectors, for control panel
	1 AC Power: On an AC power connector
Analog Audio	Input - Max. Source Level: +24dBu
	Input - Impedance: >20k Ω
	Output - Max. Source Level: +24dBu balanced +18dBu unbalanced
	Output - Impedance: <50 Ω
Enclosure	Size: 19" — 2U — mounts in a standard 19" rack
	Dimensions: 19" x 18.5" x 3.5" W, D, H