



Introduction

The Atlona **AT-OME-MS42** is a 4x2 matrix switcher with HDMI, USB-C, and DisplayPort inputs, plus HDMI and HDBaseT outputs. Part of the Omega™ Series of integration products for modern AV communications and collaboration, the OME-MS42 is HDCP 2.2 compliant and features HDBaseT extension for video up to 4K/60 4:2:0, plus embedded audio, control, Ethernet, and USB over distances up to 330 feet (100 meters). All inputs and the local HDMI output support 4K HDR and 4K/60 4:4:4 at HDMI data rates up to 18 Gbps. Additionally, 4K downscaling to 1080p @ 60, 30, or 24 Hz is available for the HDMI output when connected to an HD sink. The integrated USB extension addresses the challenge of connecting between USB devices at remote locations, and is ideal for software video conferencing and touch or interactive displays. The OME-MS42 includes USB 2.0 and USB-C interfaces for three host PCs, plus two peripheral devices such as a camera, microphone, speakerphone, or keyboard and mouse. It is ideal for video conferencing and many other 4K presentation applications with the OME-EX-RX receiver and OME-SR21 scaling receiver.

Applications

- Video conferencing**
 With the OME-EX-RX or OME-SR21 receiver, this switcher provides interfacing for local and remote USB devices for soft codec conferencing, with video and USB switched together between host PCs. As a matrix switcher with downscaling, the OME-MS42 is also ideal for hardware-based video conferencing, with the ability to route and optimize any source content to the codec far-end.
- Meeting rooms and conference rooms**
 The OME-MS42 can serve as an AV integration centerpiece in a credenza, with interfacing into sources in the rack.
- Auditoriums and lecture halls**
 This switcher can be used for presenting 4K video content through the projector, while also optimizing for a 1080p confidence monitor.

Key Features

4x2 AV matrix switcher

- HDMI, USB-C, and DisplayPort inputs.
- No need to provide adapters for USB-C or DisplayPort to HDMI.

USB-C input for AV, data, and device charging

- Provides immediate compatibility with laptops and tablets with USB-C ports supporting AV output.
- Allows clutter-free, single cable connectivity to a PC for video conferencing and collaboration.

HDBaseT and HDMI outputs with selectable AV switching modes

- HDBaseT output transmits AV, control, Ethernet, and USB up to 330 feet (100 meters) @ 1080p with CAT5e/6 or 4K/UHD using CAT6a/7 cable.
- Selectable switching modes available with auto-input selection when outputs are mirrored or matrixed.
- Enables simple configuration and effortless user operation, tailored to the specific AV application.

4K to 1080p downscaling

- Integrated video processing available on the HDMI output for down-converting 4K/UHD @ 60 Hz to 1080p.
- Ideal for applications with 1080p displays, video conferencing codecs, and other HD sink devices.

USB 2.0 interface and extension up to 330 feet (100 meters)

- Two USB type B interfaces for connection to a host PC, plus two USB type A ports for peripheral devices such as cameras, soundbars, or touch displays. USB-C input is also available for data connection to a host PC or USB peripheral.
- Provides an ideal USB integration solution for software video conferencing and other applications. A maximum data rate of 120 Mbps is supported over HDBaseT.

Remote PoE+ (Power over Ethernet) or local powering

- Industry standard IEEE 802.3at PoE+ is supplied by an OME-EX-RX receiver or OME-SR21 scaling receiver over HDBaseT.
- Also can be locally powered by the optional AT-PS-2427-D4 power supply – to supply PoE to a receiver and charge a USB-C mobile device.

Audio de-embedding

- De-embeds two channel PCM audio for the HDBaseT output and delivers to a balanced, analog audio output.
- Provides direct interfacing into an external audio system.

Automatic display control

- Automatically changes display power state based on active or standby mode of the switcher. Control signals to display are transmitted via IP, RS-232, or CEC.
- Enables effortless, automated system operation without the need for an external control system.

Specifications

Video		
Signal Type	HDMI, USB-C, DisplayPort	
HDCP	1.4/2.2	
Pixel Clock	300MHz	
UHD/HD/SD	4096x2160@60 ⁽¹⁾ /50/30/25/24Hz 3840x2160@60 ⁽¹⁾ /50/30/25/24Hz 1080p@60/59.9/50/30/29.97/25/ 24/23.98Hz 1080i@30/29.97/25Hz	720p@60/59.94/50Hz 576p@50Hz 576i@25Hz 480p@60/59.96Hz 480i@30Hz
VESA	2560x1600 2048x1536 1920x1200 1680x1050 1600x1200 1440x900 1400x1050 1280x1024	1280x800 1366x768 1360x768 1152x864 1024x768 800x600 640x480
USB-C	Up to 4K/UHD @ 60Hz	
Color Space	YUV, RGB	
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0	
Color Depth	8-bit, 10-bit, 12-bit	
HDR	HDR10, Hybrid-Log Gamma (HLG), and Dolby® Vision™ @ up to 60Hz; HDMI and USB-C inputs only	

Audio			
HDMI / HDBaseT Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Depth	Up to 24 bits		
Analog Audio			
Format	Stereo 2-Channel		
Balanced Output	+4 dBu nominal gain, +20 dB headroom		
Frequency Response	20 Hz to 20 kHz, ± 0.5 dB		
THD+N	< 0.004% at 20 Hz to 20 kHz		
SNR	> 105 dB at 1 kHz, zero clipping @ 0 dBFS, unweighted		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

USB	
Signal	2.0
Maximum Data Rate	120 Mbps
USB-C	Supports Audio, Video, device and host data, and up to 60W power charging

Control	
RS-232	Device control and configuration Bidirectional pass-through from control system over HDBaseT Supported baud rates: 2400, 4800, 9600, 19200, 38400, 57600, 115200
IP	Protocols: Https, Telnet, mDNS Modes: DHCP, Static - selectable through front panel and webGUI
CEC Support	Yes

Multi-format 4x2 matrix switcher

with HDMI, USB-C, and DisplayPort inputs, plus HDMI and HDBaseT outputs

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN/OUT	15	5	30	10
CAT5e	295	90	330	100
CAT6/6a/7	330	100	330	100

Buttons and Indicators	
Buttons: HDMI OUT and HDBaseT OUT IP MODE, RESET, and TEST	2 - momentary, tact-type 3 - momentary, recessed
Indicators: Inputs IP MODE, RESET, and TEST	8 - LED, blue 3 - LED, green

Connectors	
HDMI IN	2 - Type A, 19-pin female
DP IN	1 - DisplayPort, female
USB-C IN	1 - USB Type-C v3.1, 24-pin female, AV input (Alternate Mode)
HDMI OUT	1 - Type A, 19-pin female
HDBaseT OUT	1 - RJ45, female
USB HUB	2 - Type A, 4-pin female
USB HOST	2 - Type B, female
AUDIO OUT	1 - 5-pin captive screw, balanced / unbalanced 2-channel
RS-232	1 - 3-pin captive screw (bidirectional)
LAN	1 - RJ45, 100Base-T
PWR	1 - Internal 100-240 VAC 50/60Hz, IEC female connector

Temperature	Fahrenheit	Celsius
Operating	32 to 122	0 to 50
Storage	-4 to 140	-20 to 60
Humidity (RH)	20% to 60%, non-condensing	

Power	
Consumption	Unit only: 8.6W Full load: 104W (while powering USB-C device up to 60W, HDBaseT PoE devices up to 15W each, and USB type A devices up to 2.5W each)
Supply	Input: 100 - 240 V AC, 50/60 Hz Output: 24 V / 5A DC

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.73 x 8.64 x 10	44 x 219.5 x 254
Power Supply		

Weight	Pounds	Kilograms
Device	3.46	1.57

Certification	
Device	CE, FCC
Power Supply	CE, FCC, cULus, RoHS

Accessories

Compatible Receivers	
AT-OME-EX-RX	Omega HDMI Over HDBaseT Receiver with USB
AT-OME-SR21	Omega Scaler for HDBaseT and HDMI with USB
AT-LC-H2H-1M	LinkConnect HDMI to HDMI 1 Meter Cable
AT-LC-H2H-2M	LinkConnect HDMI to HDMI 2 Meter Cable
AT-LC-H2H-3M	LinkConnect HDMI to HDMI 3 Meter Cable
AT-LC-UC2UC-2M	LinkConnect USB-C to USB-C 2 Meter Cable
AT-LC-MDP2H-1M	LinkConnect Mini DisplayPort to HDMI 1 Meter Cable
AT-LC-MDP2H-2M	LinkConnect Mini DisplayPort to HDMI 2 Meter Cable
AT-LC-MDP2H-3M	LinkConnect Mini DisplayPort to HDMI 3 Meter Cable

Footnotes

(1) UHDp60 only supports 4:2:0 over HDBaseT.

Copyright, Trademark, and Registration

© 2021 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).