

2M / 3M / 5M / 10M / 15M / 20M / 30M VGA Cable

2L-2502/2L-2503/2L-2505/2L-2510/2L-2515/2L-2520/2L-2530

- The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. This durably constructed VGA video cable eliminates the picture ghosting and fuzzy images, guaranteeing users the ultimate AV experiences.



Features

- Optimized for analog signal transmission
- VGA cable with 15-pin male input and output
- Bend Radius: 60°*
- Outer shielded material: Al Mylar tape
- A range of cable lengths, available from 2 to 30 m
- Flame Test UL 758, CSA C22.2 No.210 compliant
- Compatible with ATEN VGA products

Note:* Swings 3000 times between angles of +/- 60 degrees, at a frequency of 40 times per minute

Specifications

| Function | 2L-2502 | 2L-2503 | 2L-2505 | 2L-2510 | 2L-2515 | 2L-2520 | 2L-2530 |
|---------------------|------------------------------------|---------|---------|---------|---------|---------|---------|
| Conductor | | | | | | | |
| Material | Tinned Copper | | | | | | |
| Conductor Diameter | 30 AWG | | | | | | |
| Jacketed | | | | | | | |
| Material | Jacket: PVC Shielding: AL-Mylar | | | | | | |
| Connectors | | | | | | | |
| Video | HDB-15 Male HDB-15 Male | | | | | | |
| Cable Length | 2 m | 3 m | 5 m | 10 m | 15 m | 20 m | 30 m |

Product information is subject to change without prior notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Publish Date: 08/2020 V2.0



© Copyright 2020 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.