

USER MANUAL

HDMI/KVM Extender over Fiber 20km (4K@60Hz)

Enjoy the vivid world

Introduction

HDMI fiber extender is a device transmitting HD audio and video signal via bidirectional single fiber cable. It transmits your HD display with the high resolutions up to 20km. It support IR, RS232 and KVM function.By using bidirectional single fiber LC interface, it has the characteristics of low cost and stable signal transmission. It can be used in security monitoring, high-definition signals between buildings, square large screens and other long-distance HDMI signal transmission fields.




Features

- * Support HDMI 4K@60Hz/HDCP2.2;
- * Support transmitter HDMI Loop out;
- * Support 3.5mm stereo output;
- * Support IR;
- * Support KVM;
- * Support RS232:
- * Comply with SFP MSA and SFF-8472 standard protocol:
- * Pure hardware design, plug and play, do not need to install additional software;
- * Support 4K to 1080P resolution (Downscaling).

Specifications

| HDMI resolution | 4K@60Hz / HDCP2.2 The highest input resolution is 3840*2160@60Hz |
|-------------------------------|---|
| Audio format | L-PCM |
| Fiber wavelength | 1310nm; 1550nm |
| Fiber transmission distance | 20km |
| The maximum operating current | 1.5A/5V DC(TX), 1.2A/5V DC (RX) |
| Operating Temperature range | (-10°C~ +55°C) |
| Dimension (L x W x H) | 106x106x17(mm) |
| Weight | TX:272.1g RX:273.1g |



Physical interface diagram



| Interface | Function |
|-----------|---------------------------|
| RS232 | RS232 port |
| USB-PC | USB port (connect to PC) |
| RST | Reset button |
| Fiber-LC | Fiber -LC type fiber port |
| Output | HDMI Signal output port |
| Input | HDMI Signal input port |
| R/L | 3.5mm stereo output |
| IR-TX | IR transmitter port |
| DC | 5V Power Interface |

| C C C C C C C C C C C C C C C C C C C | O |
|---------------------------------------|----------|
| | |
| HDWI, | |
| | |
| Fiber Extender | with KVM |
| | 4K GDHz |
| | Receiver |
| Floric | 95 |
| | 5 TO TO |
| | |
| | |

| Interface | Function |
|-----------|--|
| RS232 | RS232 port |
| USB1 | USB port (connect with keyboard and mouse) |
| USB2 | USB port (connect with keyboard and mouse) |
| RST | Reset button |
| Fiber-LC | Fiber -LC type fiber port |
| Output | HDMI Signal output port |
| R/L | 3.5mm stereo output |
| IR-RX | IR receiver port |
| DC | 5V Power Interface |

Application scene



Outdoor video wall



Shopping mall video wall



Monitor room

Package include

1: HDMI fiber extender transmitter 1PCS 2: HDMI fiber extender receiver 1PCS 3: DC 5V/2A power supply 2PCS 4: User manual 1PCS

5: IR Cable 1PAIR