

True 4K HDMI / USB HDBaseT 3.0 Transceiver

VE1843

The VE1843 is ATEN's first video transceiver and integrates the functions of a transmitter and a receiver into one unit. This combination allows users to easily configure the unit to be a transmitter or receiver depending on their AV solution, and to enjoy more flexible deployment and effective use with video matrix switches, video splitters, etc.

Designed with HDBaseT 3.0 technology, the VE1843 not only extends True 4K uncompressed signals up to 100 m over a single Cat 6a cable with zero latency, but also transmits IR, RS-232, Ethernet, independent audio, and USB signals with the latest HDBaseT standards. For stable HDMI signal transmission, the VE1843 ensures high-quality visuals and reliable extension by supporting HDCP 2.2, 3D, Deep Color, and HDR. In addition, the VE1843 is equipped with HDMI audio embedded / de-embedded functions, enabling users to flexibly adapt suitable audio / video combinations based on different environments. To ensure non-stop operations, the fanless fin heat sink design prevents overheating and thus elevates its reliability.

Empowered by the above benefits, the VE1843 increases the potential of AV applications while also streamlining complex installations. This makes the VE1843 an ideal solution for conference halls, auditoriums, lecture halls, museums, exhibition rooms, and anywhere else that requires high-quality transmission and easy-to-use application.



Front View




Rear View



Features

- Extends uncompressed True 4K HDMI signals up to 100 m over a single Cat 6a cable (HDBaseT Certified Cat 6a cable) with zero latency
- Flexible for deployment — can be configured as a transmitter or receiver depending on the AV solution
- Compliant with HDBaseT 3.0 standards — transmits high-quality video, full range IR, bi-directional RS-232, Gigabit Ethernet, independent stereo audio and USB 2.0 signals channel bypass
- HDMI (3D, Deep Color, 4K/60Hz); HDCP 2.2 compliant
- Superior video quality — up to 4096 x 2160 @ 60 Hz (4:4:4); HDR supported
- Supports HDMI audio embedded / de-embedded functions
- Supports HDMI local output
- Compliant with the USB 2.0 standard for a wide range of USB peripherals compatibility
- LED indication of HDBaseT and HDMI signal status for easier recognition
- Fanless fin heat sink enclosure — elevates durability and reliability by preventing overheating, fan malfunctions, and noises
- Firmware upgradable
- Built-in 8KV / 15KV ESD protection
- Plug-and-play
- Rack-mountable



Note: The illustrated installation is based on two VE1843 units.

Specifications

	VE1843
Video Input	
Interfaces	1 x HDMI Type A Female (Black)
Impedance	100 Ω
Max. Distance	5 m
Video Output	
Interfaces	1 x HDMI Type A Female (Black)
Impedance	100 Ω
Max. Distance	5 m
Video	
Max. Data Rate	18Gbps (6Gbps per lane)
Max. Pixel Clock	600 MHz
Compliance	HDMI (3D, Deep Color, 4K/60Hz); 4K HDR HDCP 2.2 Compliant
Max. Resolutions	4096 x 2160 @ 60Hz (4:4:4) 3840 x 2160 @ 60Hz (4:4:4)
Max. Resolutions / Distance	Up to 4K x 2K @ 60Hz (4:4:4) @ 100 m (HDBaseT ³ Certified Cat 6a cable / ATEN 2L-2920* Cat 6a cable) *2L-2920 Cat 6a cable will be coming soon. Please contact regional sales for any request.
Audio	
Input	1 x HDMI Type A Female (Black) 1 x Stereo Audio (mini stereo jack female, Green)
Output	1 x HDMI Type A Female (Black) 1 x Stereo Audio (mini stereo jack female, Green)
Connectors	
Unit to Unit	1 x RJ-45 Female
Power	1 x DC Jack (Black) with locking
Control	
RS-232 Channel	Connector: 1 x Terminal Block, 3 pole Baud Rate: 19200, Data Bits:8, Stop Bits: 1, no parity and flow control
IR Channel	1 x Mini Stereo Jack Female, (Bi-directional, Black) 30K – 56 KHz full range transmission
Ethernet Channel	1 x GbE (RJ-45 Female)
USB Channel	1 x USB Type B Female (White, Host) 1 x USB Type A Female (White, Device)
Switches	
Selection	1 x Slide Switch - Tx (Be a Transmitter) / Rx (Be a Receiver) selection
Mode Selection	1 x Slide Switch - HDMI Audio Embed or De-embed ON/OFF selection
Firmware Upgrade	1 x Slide Switch - ON/OFF
Long Reach Mode Switch	1 x Slide Switch - ON/OFF (Reserved)
LEDs	
Power	1 x Tx (Transmitter, Green) 1 x Rx (Receiver, Green) NOTE: When Tx (or Rx) Power LED On, it means VE1843 switch to Tx (or Rx)
Link	1 x Tx (Transmitter, Orange) 1 x Rx (Receiver, Orange)
Video Output	1 x Rx HDMI OUT (Receiver, Orange)
Video Input	1 x Tx HDMI IN (Transmitter, Orange)
Power Consumption	DC 12V: 6.45W: 40BTU
Environmental	
Operating Temperature	0 – 40°C
Storage Temperature	-20 – 60°C
Humidity	0 – 80% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	0.64 kg
Dimensions (L x W x H)	17.15 x 15.09 x 3.00 cm

ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datung Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Product information is subject to change without prior notice.

Released: 08/2021 V1.0

© Copyright 2021 ATEN® International Co. Ltd.
 ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.
 The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are
 trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

