



Large Venue Projector

DU7099Z+

Super-bright LV laser projector with rich connectivity and 20,000 hours of operational time & virtually maintenance free performance.

Features

- Solid state laser phosphor light source for reliable projection and performance
- Environmentally friendly lamp-less design that is mercury-free and energy efficient
- DLP® and BrilliantColor™ technologies for high-performance projection
- Brightness 8,000 lumens with a high 3,000,000:1 contrast ratio for an amazing image quality
- Almost maintenance-free with up to 20,000 hours of operating time
- Native WUXGA resolution with up to UHD-4K video signal transmission through HDBaseT™ and HDMI v2.0 interface
- Embedded smart sensor detects the brightness levels and automatically adjusts the output levels to ensure a constant bright image
- Powered zoom, focus and lens shift (horizontal/vertical) for easy adjustment and positioning flexibility
- Lens Positioning Memory for quick recall of user defined lens positions (focus, zoom and lens shift)
- Distorted and trapezoid image issues are easily corrected with HV keystone and 4-corner adjustments
- High Dynamic Range (HDR10) delivers enriched brightness and vibrancy for precise natural colors
- Full suite of display connectivity inputs and outputs including: HDMI v2.0, DVI-D, HDBaseT™, Component (5 BNC), VGA-In/Out
- HDBaseT™ interface with support for distribution of digital HD video content over standard CAT5e/6 LAN cable
- 3D compatibility with DLP® Link™ and HDMI 2.0 technology support (Blu-ray, side by side, frame packing, top and bottom) for dazzling and realistic life-like images
- Portrait mode projection allows the projector to be easily setup and installed in a 90° installation & 360° operation and projection design for set up in all angles
- Built-in 12V trigger for convenient screen control
- Ten (10) interchangeable lens options with quick touch lens release design for easy lens removal and re-installation
- Airtight sealed engine and filter-less design for improved performance against fighting dust and fibers
- Optimized system layout with high efficiency cooling system
- 24/7 continuous operation with no downtime
- Network ready for integration and system administration via RJ45
- Remotely manage and monitor a location's networked projectors from a centralized PC with Vivitek Projector Control Suite - a free companion app for Windows OS
- Supported Art-Net protocol with DMX controller for Stage Console system
- Usage time & power level locked provide convenient settings for rental market

Photos



Specifications

Display Type	Single Chip 0.67" DLP Technology by TI	
Brightness**	8,000 Lumens	
Native Resolution	WUXGA (1920 x 1200)	
Maximum Resolution	UHD (3840x2160) @60Hz	
Contrast Ratio	1,300:1 (Native) / 20,000:1 (Dynamic) / 3,000,000:1 (Full On/Off)	
Laser Life/Type	Up to 20,000 hours (Laser Phosphor Light Engine)	
Throw Ratio*	1.54 - 1.93:1	
Image Size (Diagonal)*	32.1" - 500" (Depends on option lens spec)	
Projection Distance*	1m - 20m (Depends on option lens spec)	
Projection Lens*	F = 2.02 - 2.4, f = 22.79 - 28.55mm	
Zoom Ratio*	1.25x	
Aspect Ratio	16:10	
Offset	Motorized Lens Shift	
Keystone Correction	Horizontal ±30°, Vertical ±30°	
Horizontal Frequency	15, 31 - 91.4Hz	
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz	
3D Functionality	Yes (DLP® Link™, HDMI v2.0 Blu-ray, side by side, frame packing, top and bottom)	
Lens Shift Range**	V: Bottom 50% to Top 70%, H: Left 15% to Right 15%	
Computer Compatibility	VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, 1080P, WUXGA, 4K@60Hz, Mac	
I/O Connection Ports	HDMI v2 (x2) (HDCP v2.2 Compliant), DVI-D, Component (5 BNC) (RGBHV), 3D-Sync-In, VGA-In, Audio-In (Mini-Jack), Monitor-Out, Audio-Out RCA (L/R), 3D Sync-Out, USB Type A Power (5V/1.5A), 12V Trigger, RS-232-In, RS-232-Out, Wired Remote-In, Wired Remote-Out, HDBaseT™, RJ45 (LAN), USB (Service)	
Projection Method	Table Top, Ceiling Mount, Portrait (Front or Rear)	
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock	
Dimensions (WxDxH)	470 x 517 x 202mm (18.5" x 20.3" x 7.9")	
Weight	20.6kg (45.4lbs)	
Available Colors	White (DU7099Z-WH), Black (DU7099Z-BK)	
Speakers	10W x2	
Noise Level	34dB \ 32dB (Normal \ Eco Mode)	
Power Supply	AC 100-240V, 50/60Hz	
Power Consumption	Normal	465W@110Vac
	Network Standby	Less than 2W
	Eco Standby	Less than 0.5W
Environmental Conditions	Operating	At temperature 0 to 40°C, relative humidity 10% to 85%, non-condensation
	Storage	At temperature -10 to 60°C, relative humidity 5% to 95%, non-condensation
Standard Accessories	AC Power Cord, Remote Control w/Batteries, Lens Cap, Documentation Kit	
Optional Accessories	Interchangeable Lens Options (x10) including: 0.38:1 / 0.47~0.5:1 / 0.77~1.1:1 / 1.1~1.3:1 / 1.25~1.6:1 / 1.54~1.93:1 / 1.93~2.9:1 / 2.22~3.67:1 / 3.58~5.38:1 / 5.31~8.26:1 /	

* Note: Standard Lens

**Note: Brightness specifications are in compliance with ISO 21118 standards is equal to ISO lumens

© 2023 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.