

### **PANELS**





Front View


Rear View

This HDBaseT Wall Plate Switch with Signal Management is an HDMl and VGA switch with audio embedding and HDBaseT output. The wall plate is designed for use with US two-gang sized enclosures.

This transmitter can send uncompressed highdefinition video/audio over a single cable up to a distance of 100 meters at 1080p@60Hz. High bandwidth 4K UHD+ HDMI video sources, up to and including 4K@60Hz (4:4:4, 8-bit), can be supported and will be automatically converted to 8-bit color, or the 4:2:0 color space when necessary for transmission compatibility.

Signal management features such as automatic switching based on active signal and hot plug detection enable convenient hands-free operation. Additional functionality such as EDID management, HDCP management and basic signal event automation (which can send customized RS-232 or CEC commands to external devices automatically) is also available.

## **DIAGRAM**



### **FEATURES**

- Wall plate is designed for US two-gang sized enclosures
- Supports HDMI input resolutions up to 4K@60Hz (4:4:4, 8-bit)
- Supports VGA input resolutions up to WUXGA (RB)
- · Supports CEC bypass and User activated information OSD
- Unit may be powered locally or via 48V PoH from a compatible HDBaseT Receiver (PSE)
- Supports manual input selection or automatic input selection with hot plug detection
- Basic signal event automation (via RS-232 or CEC w/ compatible Receiver)
- USB port supports firmware update and powering of 5V/500mA devices

# **SPECIFICATIONS**

SPECIFICATIONS			
Interfaces			
Input Port	2 HDMI (Type-A) 1 VGA (HD-15) 1 Stereo Audio (3.5mm)		
Output Port	1 HDBaseT (RJ-45) 1 LAN (RJ-45)		
Video			
HDMI Compliance	HDMI 2.0 (DVI 1.0)		
<b>HDCP Compliance</b>	2.x		
Input Signal Types	HDMI	4K@60 8-bit YUV 4:4:4	
Output Signal Types	HDBaseT	4K@60 8-bit YUV 4:2:0	

Power		
Maximum Output	HDBaseT	4096×2160p@30
	VGA	1920x1200@60
Maximum Input	HDMI	4096×2160p@60
		Resolutions
Output Signal Types	HDBaseT	4K@60 8-bit YUV 4:2:0
Input Signal Types	HDMI	4K@60 8-bit YUV 4:4:4

12V/3A	
23.7W	
Aluminum	
	23.7W

Chassis Material	Aluminum
Chassis Color	White
Dimensions (W×H×D)	92mm× 104mm× 50mm
Weight	250g

### ORDERING INFORMATION

ONDERING IN ONMATION		
Model No.	Product Description	
CH-2537TXWPUD	UHD HDMI/VGA over HDBaseT Wallplate Transmitter (PD)	
CH-2527RX	HDR HDMI over HDBaseT Receiver with IR, RS-232, LAN $\&$ PoH (PSE)	

