

ML1704

17" LCD 4 Port KVM Switch (Single Rail, VGA Series)

NEXIS



- Front LCD Console (Keyboard, Mouse, 17" monitor) + KVM Module design(1/4/8/16ports); It's very flexible and convenient for combination;
- Extra prepositive USB mouse interface;
- Single port length: 462.6mm; Multi-ports length: 611mm
- 1U 19" Rack mount design

SPECIFICATION

17" LCD Console

Type	17" LCD Console
Ratio	4:3
Video	SXGA TFT-LCD
Visible Square	337.920(H) × 270.336(V)
Resolution	1280x1024@60HZ (Optimum) /1920x1200@60HZ(Max) 16.7M (RGB 6 bit + Hi_FRC)
LCD Monitor	Support Color Contrast Backlight Pixel Pitch LED MTBF Input Power
	1000 : 1 (Typ) LED 0.264x0.297mm 100,000 hours 12V
Keyboard (demountable design)	Keyboard Compatible Port Using life Type Port
	100Keys, detachable (9different languages for choose) WindowsMe/NT/2000/XP, WIN7, Server2003, WIN8/8.1, WIN10, Linux OS Standard PS/2; USB >1,000,000 Times Touch Pad Standard PS/2
Mouse	X/Y Resolution Using life
	>1000dots/inch, (40x40/mm) >1,000,000 Times
Dimension	407x445x45mm
Weight	6.15kg

KVM Module

Type	4 Port KVM Swtich 4 64
Computer Connection	Direct Max.
CPU Port Selection	OSD, Front button, Hotkey, IP Remote (optional) DB 37 pin 4 x VGA DB15, Female 1 x DC Jack 1 x RJ45(Optional)
Connectors	Power Network Port Port Selection KVM Reset
	KVM Panel Digital keys KVM Panel Function keys 1 x semi-embedded key 1 x semi-embedded key
Switch	IP Module Reset IP Module Default Selected Online IP Network Keyboard/Mouse
	Nixie Tube Display 4 x Red 1 x Green, 1 x Orange USB, PS/2 1920x1200@60HZ 3, 5, 10, 15, 20, 30, 40, 60s (3s by default) -10-50 °C -20-60 °C 0-80%RH, No Condensation Metal
Scan time interval	
Operation Environment	Operating Temp. Storage Temp. Humidity
	148.4x445x45mm 2.7kg
Physical Properties	Housing Dimension Weight