

ML1904

19" LCD KVM Switch (Single Rail, VGA Series)

NEXIS



- Front LCD Console (Keyboard, Mouse, 19" monitor) + KVM Module design(1/4/8/16ports); It's very flexible and convenient for combination;
- IP optional (IP card could be installed inside KVM module);
- Extra prepositive USB mouse interface;
- Single port length: 462.6mm; Multi-ports length: 611mm

SPECIFICATION

19" LCD Console

Type	18.51" LCD Console
Ratio	16:9
Video	Wide AHVA TFT-LCD
Visible Square	409.8(H) × 230.4(V)
Resolution	1366x768@60HZ (Optimum) /1920x1200@60HZ(Max) 16.7M True 8 bit
LCD Monitor	Support Color Contrast Backlight Pixel Pitch LED MTBF Input Power
	1000 : 1 (Typ) LED 300x300um 100,000 hours 12V
Keyboard (demountable design)	Keyboard Compatible Port Using life Type Port
	100Keys, detachable (9 different languages for choose) Windows Me/NT/2000/XP, WIN7, Server2003, WIN8/8.1, WIN10 Standard PS/2; USB >1,000,000 Times Touch Pad Standard PS/2
Mouse	X/Y Resolution Using life
	>1000dots/inch, (40x40/mm) >1,000,000 Times
Dimension	407x445x45mm
Weight	6.07kg

KVM Module

Type	4 Port KVM Switch 4 64
Computer Connection	Direct Max.
CPU Port Selection	OSD, Front button, Hotkey, IP Remote (optional) DB 37 pin
Connectors	4 x VGA DB15, Female 1 x DC Jack 1 x RJ45(Optional) KVM Panel Digital keys KVM Panel Function keys 1 x semi-embedded key 1 x semi-embedded key Nixie Tube Display 4 x Red 1 x Green, 1 x Orange USB, PS/2
Switch	Console Computer Power Network Port Port Selection KVM Reset IP Module Reset IP Module Default Selected Online IP Network Keyboard/Mouse
LED's	1920x1200@60HZ 3, 5, 10, 15, 20, 30, 40, 60s (3s by default) -10-50° C -20-60° C
Using	Resolution (Max)
Using	Scan time interval
Analog Mode	0-80%RH, No Condensation
Resolution (Max)	Metal
Scan time interval	148.4x445x45mm
Operation Environment	Operating Temp. Storage Temp. Humidity
	2.7kg
Physical Properties	Housing Dimension Weight